

Stainless Steel Panel PC — A15-SST



Features

- Intel® Atom™ N270 1.6GHz processor
- 1024 x 768 (XGA) TFT, 400 cd/m², 50,000 hours
- DC 11~32V
- Stainless Steel chassis, fan-less design
- VESA mount, IP65 except I/O side
- Suitable for Food and Processing, Pharmaceutical applications

Specifications

CPU Type	Intel® Atom™ N270 1.6GHz processor built-in, FSB 533 MHz
Chipset	Intel® 945GSE + ICH7M
Memory	1 x 200-pin 400/533 MHz SO-DIMM slot up to 2GB, default 1GB/533 MHz
I/O Interface	4 x USB 2.0 type A 2 x RJ45 1 x DB9 RS232 (COM 1) 1 x DB9, COM2 (RS232/422/485 selectable, default RS232) 1 x VGA 1 x MIC, line-in, line-out 1 x Power Switch (ATX) 1 x 3-pin DC power input terminal
Display	15" TFT-LCD, 1024 x 768 Brightness 400 (cd/m ²) Backlight lifetime 50,000 hours Viewing angle 160/145 (H°/V°) Contrast ratio 800:1
Touch Screen	5-wire resistive type
Power Requirement	DC 11~32V, 33.6W
Construction	Stainless steel front bezel and aluminum extrusion back cover
Net Weight	7.2 Kgs
Mounting	VESA 75 x 75 mount
Dimensions	398(W) x 316.0(H) x 56.0(D) mm
Operating Temperature	0 ~ 50 °C
Storage Temperature	-20 ~ 60 °C
Relative Humidity	10 to 90% RH (non-condensing) @40 °C
Certification	CE/FCC class A

Ordering Information

PP-A15NS	15", 1024 x 768 Intel® Atom™ N270 1.6GHz ultra slim IP 65, stainless steel chassis, fan-less panel PC with touch screen
-----------------	---

