



Features

- Intel ATOM N2600 1.6 GHz Dual Core Processor
- 15" TFT, 1024x768 (4:3), 350 cd/m², 50,000 hours
- DC 9~36V
- Aluminum chassis, fan-less design
- Panel or VESA mount, IP65 front bezel
- Suitable for industrial applications

Specifications

CPU Type	Intel® ATOM™ N2600 1.6 GHz Dual Core Processor
Chipset	Intel® NM10
Memory	2GB
Graphics	Intel® NM10 Build-in
I/O Interface	2 x USB 2.0 type A, USB4/5 RS-232/422/485 DB-9, COM1, Default RS-232 RS-232 DB-9, COM2 1 x Line out phone jack 2 x GbE RJ-45
Expansion	1 x Mini-PCIe Slot (Half-size)
Display	15" TFT-LCD, 1024 x 768 Luminance 350 (cd/m ²) View angle 160/145 (H°/V°) Backlight Lifetime 50,000 hours Contrast ratio 800:1
Touch Screen Type	5-wire resistive touch
Power	9~36V DC
Construction	Silver aluminum front bezel and chassis
Net Weight(Kgs)	6.3 Kg
Mounting	Panel Mount, VESA 100 x 100
Dimensions	410.0 (W) x 310.0 (H) x 55.0 (D) mm
Operating Temp.	0°C ~ 50°C
Storage Temp.	-20° ~ 60°C
Humidity	10% to 90% @ 40°C (non-condensing)
Certification	CE/FCC Class A

Ordering Information

PP-A15

15" TFT 1024 x 768 fan-less HMI with ATOM N2600 1.6 GHz CPU Dual Core, 2GB memory, resistive touch screen, 9~36V DC input, silver aluminum front bezel and chassis, IP65 front bezel.

